

# Frabo Adesivi Superpivigum E/197

INGREDIENTS	CAS NO	%	8HR OEL
acetone	67-64-1	73-85	1185 mg/m3



UN No: 1133 Hazchem Code: •3YE

DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: II Poisons Schedule: S5



#### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

#### **HEALTH HAZARD INFORMATION**









Effects:

Irritating to eyes.

Vapours may cause drowsiness and dizziness.

Chronic **Health Effects:**  Repeated exposure may cause skin dryness and cracking.

\* - limited evidence

#### PRECAUTIONS FOR USE















Appropriate
engineering
controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.BUTYL 2.BUTYL/NEOPRENE 3.PVA

Respirator:

Storage and

Transportation:

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container in a well ventilated place. Keep away from sources of ignition. No smoking.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

### **PROPERTIES**







## **EMERGENCY**











### **FIRST AID**

Swallowed:	Give water (if conscious). URGENT MEDICAL
	ATTENTION.

Eye: Wash with running water.

Remove contaminated clothing. Wash with soap & Skin:

water.

Fresh air. Rest, keep warm. If breathing shallow, Inhaled:

give oxygen. Medical attention.

**Advice To** Doctor:

Spills and

Disposal:

No antidote. Supportive care.

Fire Fighting: Keep containers cool. Foam.

> Spilled liquid has low boiling temperature and evaporates quickly. Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its

container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

### SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Explosive

x x

Toxic

Radioactive Oxidizing

X X

- Must not be stored together