

Nalco Visco 3554 HFP

INGREDIENTS	CAS NO	%	8HR OEL
tallow alkylamine, ethoxylated	61791-26-2	10-30	-
toluene-4-sulfonic acid	104-15-4	<5	-
quaternary ammonium compound, proprietary	Not Available	10-30	-



UN No: 3265
 Hazchem Code: 2X
 DG Class: 8
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation and if swallowed.
 Causes burns.
 Risk of serious damage to eyes.

PRECAUTIONS FOR USE



Appropriate engineering controls:

General Exhaust Ventilation adequate.

Glasses:

Consider full face-shield.

Gloves:

PVC chemical resistant type.

Respirator:

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion Hazard:

Toxic smoke/fumes in a fire.
 Attacks metals to liberate hydrogen.

Environment:

Toxic to aquatic organisms. Use appropriate container to avoid environmental contamination.

PROPERTIES



Mixes with water.
 Corrosive.
 Acid.
 Alkaline. Combustible.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	AK-P
Fire Fighting:	Water spray/ fog.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Neutralize with soda ash/ lime.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive



Radioactive



Oxidizing

x	x	x
---	---	---

x — Must not be stored together