

Hempel Hempadur Primer 15309

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	12.5-15	350 mg/m3
propylene glycol monomethyl ether acetate, alpha-isomer	108-65-6	3-5	274 mg/m3
ethylbenzene	100-41-4	3-5	434 mg/m3
zinc phosphate	7779-90-0	0.5-1	2 mg/m3



UN No: 1263 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION













Harmful by inhalation. Harmful in contact with skin.

Irritating to eyes. **Acute Health** Effects: Irritating to skin.

> May cause SENSITISATION by skin contact. HARMFUL-May cause lung damage if swallowed.

Chronic **Health Effects:** Limited evidence of a carcinogenic effect.

* - limited evidence

PRECAUTIONS FOR USE





Fire/Explosion

Hazard:











Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.TEFLON 2.PVA
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Repo

Toxic smoke/fumes in a fire.

Flammable.

PROPERTIES





Liquid.Flammable.







FIRST AID

Give water (if conscious). Seek medical advice. Swallowed: Do NOT give milk or oil.

Do NOT give alcohol.

Wash with running water. Eye:

Remove contaminated clothing. Wash with soap & Skin:

Fresh air. Rest, keep warm. If breathing shallow, Inhaled: give oxygen. Medical attention.

Advice To Evaluate for respiratory distress. Consider lavage

with cuffed tube. NO adrenalin. Doctor:

Fire Fighting: Foam.

> Eliminate ignition sources. Prevent from entering drains. Spills and Contain spillage by any means. Disposal:

> > X

Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive









- Must not be stored together

Toxic

X