

AGS Door-Ease Stick Lubricant

INGREDIENTS	CAS NO	%	8HR OEL
paraffin wax	8002-74-2	30-45	2 mg/m3
zinc naphthenate	12001-85-3	1-5	-
petroleum Oil	Not Available	30-45	-
microcrystalline wax	63231-60-7	15-20	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type. Leather Gloves.
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.

PROPERTIES



Does not mix with water.
Floats on water. Combustible.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Skin:	Wash with soap For burns: Apply cold water. Do NOT remove clothes from area. Cover wound. NO OINTMENTS.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Emesis generally unnecessary. Debride for subcutaneous injection.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Sweep shovel to safe place.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Oxidizing

x

x — Must not be stored together