

MA440/441 Activator , adhesive filler

INGREDIENTS	CAS NO	%	8HR OEL
methyl methacrylate	80-62-6	45-85	208 mg/m3
zinc dimethacrylate	Not Available	1-10	-



UN No: 1133
 Hazchem Code: •3YE
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: II
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Irritating to eyes, respiratory system and skin.
 May cause SENSITISATION by skin contact.
 Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE



Appropriate engineering controls:

General Exhaust Ventilation adequate.

Glasses:

Consider chemical goggles.

Gloves:

1.PE/EVAL/PE 2.PVA 3.TEFLON

Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE.
 Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.

PROPERTIES



Liquid.

Does not mix with water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Keep containers cool. Foam.
Spills and Disposal:	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

			
Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together