

Halliburton Coilgard

INGREDIENTS	CAS NO	%	8HR OEL
KEROSENE JET A-1	8008-20-6	10-30	5 mg/m3
diethylamine	109-89-7	1-5	30 mg/m3
XYLENE	1330-20-7	1-5	350 mg/m3
ISOPROPYL ALCOHOL	67-63-0	1-5	983 mg/m3



UN No: 2924
 Hazchem Code: •3W
 DG Class: 3
 Subsidiary Risk: 8
 Packing Group: III
 Poisons Schedule: S5



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

PROPERTIES



Liquid. Corrosive. Flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Pollutant. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing

x

x

x

x

x — Must not be stored together

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation.
 Causes burns.
 Risk of serious damage to eyes.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 Possible risk of harm to the unborn child.

* — limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider full face-shield.

Gloves:

1.PE/EVAL/PE 2.PVA 3.TEFLON

Respirator:

Type AK Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

Environment:

May cause long-term adverse effects in the environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.