

# Lubriplate 130-A; 130-AA

INGREDIENTS	CAS NO	%	8HR OEL
naphthenic distillate, heavy, hydrotreated (severe)	64742-52-5.	75-90	5 mg/m3
naphthenic distillate, light, hydrotreated (severe)	64742-53-6.	25-50	5 mg/m3
antimony diamyldithiocarbamate	15890-25-2	1-3	0.5 mg/m3
zinc oxide	1314-13-2	5-8	10 mg/m3



UN No: 3077 Hazchem Code: 2Z DG Class: 9

Subsidiary Risk: None Packing Group: III Poisons Schedule: \$5

#### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## **HEALTH HAZARD INFORMATION**







**Acute Health** Effects:

Harmful by inhalation. Harmful if swallowed.

Vapours may cause drowsiness and dizziness.

### PRECAUTIONS FOR USE











Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type. Neoprene.
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point

## **PROPERTIES**







Liquid. Does not mix with water. Floats on water. Combustible.

### **EMERGENCY**









# **FIRST AID**

Swallowed:	Give water (if conscious). Seek medical advice.	
Eye:	Wash with running water.	
Skin:	Remove contaminated clothing. Wash with soap & water.	
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.	
Advice To Doctor:	Emesis generally unnecessary. Debride for subcutaneous injection.	
Fire Fighting:	Keep containers cool. Water spray/ fog.	
Spills and Disposal:	Eliminate ignition sources. Pollutant. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.	

### SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS





Explosive Radioactive

х х

x - Must not be stored together