

ETHYL ACETATE

INGREDIENTS	CAS NO	%	8HR OEL
ethyl acetate	141-78-6	>99	720 mg/m3



UN No: 1173
 Hazchem Code: 3YE
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: II
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects: Irritating to eyes.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects: Repeated exposure may cause skin dryness and cracking.
 * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls: Local Exhaust Ventilation recommended.

Glasses: Consider chemical goggles.

Gloves: 1.PE/EVAL/PE 2.PVA 3.TEFLON

Storage and Transportation: Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.
 Keep out of reach of children.
 Keep container in a well ventilated place.
 Keep away from sources of ignition. No smoking.

Fire/Explosion Hazard: HIGHLY FLAMMABLE.
 Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.
 In case of fire and/or explosion, DO NOT BREATHE FUMES.

PROPERTIES



Liquid.
 Does not mix with water.
 Floats on water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Fire Fighting:	Keep containers cool. Foam.
Spills and Disposal:	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together