

M-I Drilling Fluids VG-Supreme

INGREDIENTS	CAS NO	%	8HR OEL
silica crystalline - quartz	14808-60-7	0-6	0.1 mg/m3
tallow alkylmethylammonium chloride/ montmorillonite	68153-30-0	>94	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Respirator:	Particulate. (AS/NZS 1716 & 1715, EN 143:2000 & 149:001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.

PROPERTIES



Solid. Does not mix with water. Sinks in water. Combustible.

EMERGENCY



FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Avoid dust. Sweep shovel to safe place.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together