

Nalco Thermogain EC3019A

INGREDIENTS	CAS NO	%	8HR OEL
naphthalene	91-20-3	5-10	52 mg/m3
aromatic 150	64742-95-6.	30-60	-



UN No: 3082 Hazchem Code: •3Z DG Class: 9

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable

HEALTH HAZARD INFORMATION











Irritating to respiratory system.

HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Chronic **Health Effects:** Limited evidence of a carcinogenic effect. Repeated exposure may cause skin dryness and cracking.

* - limited evidence

PRECAUTIONS FOR USE













Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.TEFLON
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.
Environment:	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ **3**: High
- ▶ 4: Extreme

PROPERTIES







Liquid.

Does not mix with water. Floats on water.Combustible.

EMERGENCY









FIRST AID

Give water (if conscious). Seek medical advice.

Swallowed: Do NOT give milk or oil.

Do NOT give alcohol.

Eye: Wash with running water.

Remove contaminated clothing. Wash with soap & Skin:

water.

Fresh air. Rest, keep warm. If breath shallow, give Inhaled:

oxygen. Medical attention.

Evaluate for respiratory distress. Consider lavage **Advice To**

with cuffed tube. NO adrenalin. Doctor:

Keep containers cool. Fire Fighting:

Foam.

Eliminate ignition sources.

Pollutant.

Spills and Prevent from entering drains.

Disposal: Contain spillage by any means.

> Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Explosive Radioactive Oxidizing x x x