

## PPG Satinhide INT LTX S/G - Pastel Base

INGREDIENTS	CAS NO	%	8HR OEL
titanium dioxide	98084-96-9	10-30	10 mg/m3
kaolin	1332-58-7	0.5-1.5	10 mg/m3
#30nonhaz	Not Available	balance	-
propylene glycol	57-55-6	0.5-1.5	474 mg/m3

UN No: **Not Applicable**  
 Hazchem Code: **Not Applicable**  
 DG Class: **Not Applicable**  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: **Not Applicable**  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION

## PRECAUTIONS FOR USE



<b>Appropriate engineering controls:</b>	Local Exhaust Ventilation recommended.
<b>Glasses:</b>	Consider chemical goggles.
<b>Gloves:</b>	1.PE/EVAL/PE
<b>Storage and Transportation:</b>	Store in cool, dry, protected area.
<b>Fire/Explosion Hazard:</b>	Toxic smoke/fumes in a fire.

## PROPERTIES



Liquid. Combustible.

## EMERGENCY



## FIRST AID

<b>Swallowed:</b>	Give water (if conscious). Seek medical advice.
<b>Eye:</b>	Wash with running water.
<b>Skin:</b>	Remove contaminated clothing. Wash with soap & water.
<b>Inhaled:</b>	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
<b>Advice To Doctor:</b>	Treat symptomatically.
<b>Fire Fighting:</b>	Foam.
<b>Spills and Disposal:</b>	Spilled liquid has low boiling temperature and evaporates quickly. Eliminate ignition sources. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together