

TBM Hydraulic Assembly Lubricant

INGREDIENTS	CAS NO	%	8HR OEL
paraffinic distillate, heavy, solvent-dewaxed (severe)	64742-65-0.	NotSpec.	5 mg/m3
C.I. Solvent Red 164	71819-51-7	<3	-
interchangeable neutral oils containing	Not Available	40-70	-
acrylic copolymer	Not Available	30-60	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **None**
 Subsidiary Risk: **None**
 Packing Group: **None**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE



Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider chemical goggles.
Gloves:	LBGV2
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	Vapours/gas heavier than air. Toxic smoke/fumes in a fire.

PROPERTIES

2
Combustible.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest. Medical advice.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Foam. Dry agent.
Spills and Disposal:	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together