

GE Petromeen 4H607

INGREDIENTS	CAS NO	%	8HR OEL
ethanolamine	141-43-5	>25	7.5 mg/m ³
diethanolamine	111-42-2	<1	13 mg/m ³
monoisopropanolamine	78-96-6	>10	-



UN No: 2735
 Hazchem Code: 2X
 DG Class: 8
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation, in contact with skin and if swallowed.
 Causes burns.
 Risk of serious damage to eyes.

PRECAUTIONS FOR USE



Appropriate engineering controls:

General Exhaust Ventilation adequate.

Glasses:

Consider chemical goggles.
 Consider full face-shield.

Gloves:

1.BUTYL 2.NEOPRENE 3.VITON

Respirator:

Type AEK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion Hazard:

Toxic smoke/fumes in a fire.

PROPERTIES



Liquid.
 Mixes with water.
 Corrosive.
 Alkaline/Combustible.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Supportive care. Irrigate eyes with saline. Supportive care.
Fire Fighting:	Water spray/ fog.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Radioactive Oxidizing

x

x

x

x — Must not be stored together