

## Sealweld #5050 Ball Valve Sealant

INGREDIENTS	CAS NO	%	8HR OEL
butyl benzyl phthalate	85-68-7	1-8	-

UN No: **Not Applicable**  
 Hazchem Code: **Not Applicable**  
 DG Class: **Not Applicable**  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: **Not Applicable**  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION

## Chronic Health Effects:

May cause harm to the unborn child.  
 Possible risk of impaired fertility.

\* — *limited evidence*

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.NITRILE

## Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area.

## Fire/Explosion Hazard:

Toxic smoke/fumes in a fire.

## Environment:

Toxic to aquatic organisms.  
 May cause long-term adverse effects in the aquatic environment.  
 May cause long-term adverse effects in the environment. Use appropriate container to avoid environmental contamination.  
 Avoid release to the environment. Refer to special instructions/Safety data sheets.

## PROPERTIES



Does not mix with water.  
 Sinks in water. Combustible.

## EMERGENCY



## FIRST AID

**Swallowed:** Rinse mouth with water.

**Eye:** Wash with running water. For discomfort seek medical advice.

**Skin:** Wash with soap

**Inhaled:** Fresh air. Rest, keep warm.

**Advice To Doctor:** Treat symptomatically.

**Fire Fighting:** Foam.

**Spills and Disposal:** Eliminate ignition sources.  
 Pollutant.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Oxidizing

x

x — *Must not be stored together*