

## BASF Amerel 1500

INGREDIENTS	CAS NO	%	8HR OEL
silica amorphous	7631-86-9	15	2 mg/m <sup>3</sup>
polydimethylsiloxane	63148-62-9	85	-

UN No: **Not Applicable**  
 Hazchem Code: **Not Applicable**  
 DG Class: **Not Applicable**  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: **Not Applicable**  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION

## PRECAUTIONS FOR USE



<b>Appropriate engineering controls:</b>	Local Exhaust Ventilation recommended.
<b>Glasses:</b>	Safety Glasses. Consider chemical goggles.
<b>Gloves:</b>	PVC chemical resistant type.
<b>Respirator:</b>	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
<b>Storage and Transportation:</b>	Store in cool, dry, protected area.
<b>Fire/Explosion Hazard:</b>	Toxic smoke/fumes in a fire.

## PROPERTIES



Liquid. Does not mix with water. Combustible.

## EMERGENCY



## FIRST AID

<b>Swallowed:</b>	Rinse mouth with water.
<b>Eye:</b>	Wash with running water.
<b>Skin:</b>	Remove contaminated clothing. Wash with soap & water.
<b>Inhaled:</b>	Fresh air. Rest, keep warm.
<b>Advice To Doctor:</b>	Treat symptomatically.
<b>Fire Fighting:</b>	Foam.
<b>Spills and Disposal:</b>	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together