

## Rezitech Belzona 1591 (Ceramic XHT) Base

INGREDIENTS	CAS NO	%	8HR OEL
bisphenol F glycidyl ether/ formaldehyde copolymer	28064-14-4	10-30	-



UN No: 3082  
 Hazchem Code: •3Z  
 DG Class: 9  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: III  
 Poisons Schedule: S5



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



**Acute Health Effects:** Irritating to eyes and skin.  
 May cause SENSITISATION by skin contact.

## PRECAUTIONS FOR USE



<b>Appropriate engineering controls:</b>	Local Exhaust Ventilation recommended.
<b>Glasses:</b>	Consider chemical goggles.
<b>Respirator:</b>	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
<b>Storage and Transportation:</b>	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
<b>Fire/Explosion Hazard:</b>	Vapours/gas heavier than air. Toxic smoke/fumes in a fire.
<b>Environment:</b>	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.

## PROPERTIES



Does not mix with water.  
 Sinks in water. Combustible.  
 May form explosive peroxides.

## EMERGENCY



## FIRST AID

<b>Swallowed:</b>	Rinse mouth with water.
<b>Eye:</b>	Wash with running water.
<b>Skin:</b>	Remove contaminated clothing. Wash with soap & water.
<b>Inhaled:</b>	Fresh air. Rest, keep warm.
<b>Advice To Doctor:</b>	Treat symptomatically.
<b>Fire Fighting:</b>	Keep containers cool. Foam.
<b>Spills and Disposal:</b>	Eliminate ignition sources. Pollutant. Prevent from entering drains. Contain spillage by any means.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive   Radioactive   Oxidizing

x   x   x

x — Must not be stored together