

Metallic Welding powder 29029S

INGREDIENTS	CAS NO	%	8HR OEL
nickel fume	7440-02-0	NotSpec.	1 mg/m3
molybdenum fume	7439-98-7	NotSpec.	2 mg/m3
welding fumes	Not avail.	NotSpec.	-
aluminium fumes	7429-90-5.	NotSpec.	10 mg/m3

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Respirator:	Particulate. (AS/NZS 1716 & 1715, EN 143:000 & 149:001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.

PROPERTIES

Does not burn.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Wash with soap
Inhaled:	Blow nose. Rinse mouth with water.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Keep surrounding area cool. Water spray/fog.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together