

## SCOTCH-SEAL 800 INDUSTRIAL SEALANT

INGREDIENTS	CAS NO	%	8HR OEL
methyl ethyl ketone	78-93-3	35-50	445 mg/m <sup>3</sup>
methyl isobutyl ketone	108-10-1	3-7	205 mg/m <sup>3</sup>
calcium carbonate	471-34-1	5-10	10 mg/m <sup>3</sup>
red iron oxide	1332-37-2	1-5	5 mg/m <sup>3</sup>



UN No: 1866  
 Hazchem Code: •3YE  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: II  
 Poisons Schedule: S5



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Irritating to respiratory system.  
 Risk of serious damage to eyes.  
 HARMFUL-May cause lung damage if swallowed.  
 Vapours may cause drowsiness and dizziness.

## Chronic Health Effects:

Repeated exposure may cause skin dryness and cracking.  
 \* – limited evidence

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.PE/EVAL/PE 2.BUTYL 3.TEFLON

## Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area.  
 Restrictions on Storage apply. Refer to Full Report.

## Fire/Explosion Hazard:

HIGHLY FLAMMABLE.  
 Vapours/gas heavier than air.  
 Toxic smoke/fumes in a fire.

## Environment:

Toxic to aquatic organisms.  
 May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.  
 Avoid release to the environment. Refer to special instructions/Safety data sheets.

## PROPERTIES



Liquid. Highly flammable.

## EMERGENCY



## FIRST AID

**Swallowed:** Give water (if conscious). Seek medical advice.

**Eye:** Wash with running water.

**Skin:** Remove contaminated clothing. Wash with soap & water.

**Inhaled:** Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

**Fire Fighting:** Keep containers cool.  
 Foam.

## Spills and Disposal:

Eliminate ignition sources.  
 Consider evacuation.  
 Prevent from entering drains.  
 Contain spillage by any means.  
 Control vapour with water spray/ fog.  
 Absorb with dry agent.  
 Stop leak if safe to do so.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing

x x x x

x — Must not be stored together