

Saudi Industrial Paint Devran 744 Epoxy Tank Lining Base

INGREDIENTS	CAS NO	%	8HR OEL
n-butanol	71-36-3	<5	N/A
epoxy resin, proprietary	Not Available	40-50	-
high flash naphtha	Not Available	10-15	-



UN No: 1993
 Hazchem Code: •3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Irritating to eyes, respiratory system and skin.

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire.

PROPERTIES



Does not mix with water.
 Sinks in water. Flammable.

EMERGENCY



FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing

x x x x

x — Must not be stored together