

## Colturiet TCD

INGREDIENTS	CAS NO	%	8HR OEL
methyl isobutyl ketone	108-10-1	4-7	205 mg/m3
xylene	1330-20-7	2-5	350 mg/m3
epoxy resin	Not Available	25-40	-



UN No: 1993  
 Hazchem Code: •3Y  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: III  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION

## PRECAUTIONS FOR USE



<b>Appropriate engineering controls:</b>	Local Exhaust Ventilation recommended.
<b>Glasses:</b>	Consider chemical goggles.
<b>Gloves:</b>	1.PE/EVAL/PE 2.PVA 3.TEFLON
<b>Respirator:</b>	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
<b>Storage and Transportation:</b>	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Keep out of reach of children.
<b>Fire/Explosion Hazard:</b>	Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire.

## PROPERTIES



Liquid.  
 Does not mix with water.  
 Sinks in water. Flammable.

## EMERGENCY



## FIRST AID

<b>Swallowed:</b>	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
<b>Eye:</b>	Wash with running water.
<b>Skin:</b>	Wash with soap
<b>Inhaled:</b>	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
<b>Advice To Doctor:</b>	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
<b>Fire Fighting:</b>	Foam.
<b>Spills and Disposal:</b>	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together