

RUBBER CEMENT

INGREDIENTS	CAS NO	%	8HR OEL
heptane	31394-54-4	>80	1640 mg/m3
isopropanol	67-63-0	1.49	983 mg/m3



UN No: 1993
 Hazchem Code: •3YE
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: II
 Poisons Schedule: S5



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects: Irritating to skin.
 Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.NITRILE, PVC 2.NITRILE 3.PVC
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire.
Environment:	Very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES



Does not mix with water.
 Floats on water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	A
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Keep containers cool. Foam.
Spills and Disposal:	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together