

# **Univar Shell Omala S2 GX 220**

INGREDIENTS	CAS NO	%	8HR OEL
tetraethylenepentamine isostearamide	68784-17-8	<0.9	-
mineral oil	Not Available	>60	5 mg/m3

UN No: Not Applicable Hazchem Code: Not Applicable DG Class: Not Applicable Subsidiary Risk: Not Applicable Packing Group: Not Applicable Poisons Schedule: Not Applicable



#### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ **3:** High
- ▶ 4: Extreme

## **HEALTH HAZARD INFORMATION**

#### PRECAUTIONS FOR USE











Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	Vapours/gas heavier than air. Toxic smoke/fumes in a fire.

## **PROPERTIES**







Liquid. Does not mix with water. Floats on water. Combustible.

#### **EMERGENCY**







PST	ΛI	П

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water. For discomfort seek medical advice.
Skin:	Wash with soap
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Emesis generally unnecessary. Debride for subcutaneous injection.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so.

### SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together