

Demulsifier PSR-1100

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	5-10	350 mg/m3
isopropanol	67-63-0	10-30	983 mg/m3
isopropyl benzene - cumene	98-82-8	<1	125 mg/m3
naphthalene	91-20-3	1-5	52 mg/m3



UN No: 1993 Hazchem Code: •3YE

DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: II

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION















Acute Health Effects: Harmful by inhalation. Irritating to skin.

Risk of serious damage to eyes.

HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Chronic **Health Effects:** Limited evidence of a carcinogenic effect. Repeated exposure may cause skin dryness and

cracking.

* - limited evidence

PRECAUTIONS FOR USE

















Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.NITRILE

Respirator:

Type AB-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and

Store in cool, dry, protected area.

Transportation:

Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion

Environment:

HIGHLY FLAMMABLE.

Hazard:

Toxic smoke/fumes in a fire.

Toxic to aquatic organisms. May cause long-term adverse effects in the

aquatic environment. Use appropriate container to avoid environmental contamination.

Avoid release to the environment. Refer to special

instructions/Safety data sheets.

PROPERTIES







Does not mix with water. Floats on water. Highly flammable.











FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Fire Fighting:	Keep containers cool. Foam.
Spills and Disposal:	Eliminate ignition sources. Consider evacuation. Prevent from entering drains.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Contain spillage by any means.

Explosive

Toxic

Radioactive Oxidizing Х x

- Must not be stored together