

# Chemical Marketing Electrolyte SG: 1.1650-1.1750

INGREDIENTS	CAS NO	%	8HR OEL
sulfuric acid	7664-93-9	23.28-24.55	1 mg/m3
water	7732-18-5	76.72-75.45	-



UN No: 2796 Hazchem Code: 2R DG Class: 8

Subsidiary Risk: Not Applicable

Packing Group: II
Poisons Schedule: **S6** 



#### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- **▶ 3:** High
- ▶ 4: Extreme

### **HEALTH HAZARD INFORMATION**









Harmful by inhalation. Causes severe burns.

Risk of serious damage to eyes.

#### PRECAUTIONS FOR USE













Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider full face-shield.
Gloves:	1.NEOPRENE 2.NATURALRUBBER
Respirator:	Type E-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire. Attacks metals to liberate hydrogen.

#### **PROPERTIES**



Liquid. Corrosive. Acid.Does not burn.

# **EMERGENCY**











## FIRST AID

THIOTTHE	
Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Airway problems - 100% O2. Treat burns as thermal. Retract eyelids - irrigate 30 mins. Retract eyelids/ Irrigate 30 mins.
Fire Fighting:	Keep surrounding area cool. Water spray/fog.
Spills and Disposal:	Absorb with dry agent. Dilute with water. Neutralize with soda ash/ lime. Stop leak if safe to do so.

# SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS





Explosive Radioactive

x x

— Must not be stored together