

Pittsburgh Pittcote 300 Finish (Spray Or Trowel Grade)

INGREDIENTS	CAS NO	%	8HR OEL
Stoddard Solvent	8052-41-3.	20-40	790 mg/m3
limestone	1317-65-3	5-15	10 mg/m3
cellulose	9004-34-6	<10	10 mg/m3
bitumen (blown)	64742-93-4	40-60	-



UN No: 1999
 Hazchem Code: 2W
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Irritating to respiratory system.
 Risk of serious damage to eyes.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Limited evidence of a carcinogenic effect.
 Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

PVC chemical resistant type.

Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.
 Keep out of reach of children.
 Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable.
 Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.

Environment:

Very toxic to aquatic organisms. Use appropriate container to avoid environmental contamination.
 Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES



Liquid.
 Does not mix with water. Flammable.
 Combustible.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice.
 Do NOT give milk or oil.
 Do NOT give alcohol.

Eye:

Wash with running water (15 mins). Medical attention.

Skin:

Remove contaminated clothing. Wash with soap & water.
 For burns: Apply cold water. Do NOT remove clothes from area. Cover wound. NO OINTMENTS.

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting:

Water spray/ fog.

Spills and Disposal:

Eliminate ignition sources.
 Prevent from entering drains.
 Contain spillage by any means.
 Absorb with dry agent.
 Stop leak if safe to do so.
 This material and its container must be disposed of in a safe way.
 To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together