

Exxon Asia Isopar G Fluid

INGREDIENTS	CAS NO	%	8HR OEL
naphtha petroleum, heavy, hydrotreated	64742-48-9.	>90	5 mg/m3
n-nonane	111-84-2	1-5	1050 mg/m3



UN No: 3295 Hazchem Code: 3Y DG Class: 3 Subsidiary Risk: None Packing Group: III

Poisons Schedule: \$5

NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ **3**: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION









Acute Health Effects: HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Danger of cumulative effects.

Chronic Health Effects: Repeated exposure may cause skin dryness and cracking.

* - limited evidence

PRECAUTIONS FOR USE













Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

PVC chemical resistant type.

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Not recommended for interior use on large surface areas. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Not recommended for interior use on large surface areas. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES







Liquid. Does not mix with water.Flammable.

EMERGENCY







FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice. Do

NOT give milk or oil. Do NOT give alcohol.

Eye:

Wash with running water.

Skin:

Remove contaminated clothing. Wash with soap &

Foam.

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow,

give oxygen. Medical attention.

Advice To Doctor: Evaluate for respiratory distress. Consider lavage

with cuffed tube. NO adrenalin.

Fire Fighting:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Not

Spills and Disposal:

recommended for interior use on large surface areas. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects

contaminated by this material, use water and

detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Explosive

Toxic

Radioactive Oxidizing x x x x

- Must not be stored together