

Saudi Factory Electric & Electronic 2000

INGREDIENTS	CAS NO	%	8HR OEL
trichloroethylene	79-01-6	20-30	54 mg/m3
perchloroethylene	127-18-4	40-60	340 mg/m3
mineral spirit	64475-85-0	25-35	-



UN No: **3082**
 Hazchem Code: **•3Z**
 DG Class: **9**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **III**
 Poisons Schedule: **S6**



NFPA Rating:

- ▶ **0:** Minimum
- ▶ **1:** Low
- ▶ **2:** Moderate
- ▶ **3:** High
- ▶ **4:** Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Irritating to eyes.
 Irritating to skin.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.
 Possible risk of irreversible effects.

Chronic Health Effects:

May cause CANCER.
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

* – limited evidence

PROPERTIES



Liquid. Does not mix with water. Sinks in water.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). URGENT MEDICAL ATTENTION. Do NOT give milk or oil. Do NOT give alcohol.

Eye:

Wash with running water.

Skin:

Remove contaminated clothing. Wash with soap & water.

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Treat symptomatically. NO adrenalin. Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. Assess airway and circulation. Lavage with cuffed tube. NO adrenaline. Assess airway and circulation. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting:

Keep containers cool.

Spills and Disposal:

Eliminate ignition sources. Pollutant. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.VITON/CHLOROBUTYL 2.PVA

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Radioactive

x

x

x — Must not be stored together