

PPG Industries PPG Thinner 20-05

INGREDIENTS	CAS NO	%	8HR OEL
naphtha petroleum, heavy, hydrotreated	64742-48-9.	>60	5 mg/m3
trimethylbenzene (mixed isomers)	25551-13-7	1-10	123 mg/m3
1,2,4-trimethyl benzene	95-63-6	1-10	-
naphtha petroleum, light aromatic solvent	64742-95-6.	1-10	-



UN No: 1263
 Hazchem Code: •3Y
 DG Class: 3
 Subsidiary Risk: **None**
 Packing Group: III
 Poisons Schedule: **S5**

**NFPA Rating:**

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

**Acute Health Effects:**

Irritating to eyes.
 Irritating to respiratory system.
 Irritating to skin.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PRECAUTIONS FOR USE

**Appropriate engineering controls:**

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

PVC chemical resistant type.

Respirator:

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES



Liquid. Does not mix with water. Floats on water. Flammable.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). URGENT MEDICAL ATTENTION. Do NOT give milk or oil. Do NOT give alcohol.

Eye:

Wash with running water.

Skin:

Remove contaminated clothing. Wash with soap & water.

Inhaled:

Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

Fire Fighting:

Foam.

Spills and Disposal:

Spilled liquid has low boiling temperature and evaporates quickly. Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing

x — Must not be stored together