

## Permatex PX Form-A-Gasket Sealant #2 11 Oz.

INGREDIENTS	CAS NO	%	8HR OEL
METHYL ISOBUTYL KETONE	108-10-1	0.1-1	205 mg/m3
ISOPROPYL ALCOHOL	67-63-0	1-5	983 mg/m3
ETHYL ALCOHOL	64-17-5	5-10	1880 mg/m3
METHANOL	67-56-1	0.1-1	262 mg/m3

UN No: **Not Applicable**  
 Hazchem Code: **Not Applicable**  
 DG Class: **Not Applicable**  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: **Not Applicable**  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

May cause SENSITISATION by skin contact.

## Chronic Health Effects:

Limited evidence of a carcinogenic effect.  
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
 May cause harm to the unborn child.

\* – limited evidence

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.PE/EVAL/PE 2.PVDC/PE/PVDC

## Respirator:

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children.

## Fire/Explosion Hazard:

Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

## PROPERTIES



Liquid.Combustible.

## EMERGENCY



## FIRST AID

## Swallowed:

Give water (if conscious). Seek medical advice.

## Eye:

Wash with running water.

## Skin:

Flood body with water. Remove contaminated clothing. Wash with water

## Inhaled:

Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

## Advice To Doctor:

Treat symptomatically. Decontaminate with ipecac or lavage. Ethanol therapy.

## Fire Fighting:

Foam.

## Spills and Disposal:

Eliminate ignition sources. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive



Radioactive

x

x

x — Must not be stored together