

NALCO 5328

INGREDIENTS	CAS NO	%	8HR OEL
diethylaminoethanol	100-37-8	<5	48 mg/m3
sodium sulfite	7757-83-7	5-10	-
potassium hydroxide	1310-58-3	<5	N/A
sodium tripolyphosphate	7758-29-4	NotSpec.	-



UN No: 3266
 Hazchem Code: 2X
 DG Class: 8
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Causes burns.
 Risk of serious damage to eyes.
 Possible risk of irreversible effects.

PRECAUTIONS FOR USE



Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider full face-shield.
Gloves:	1.BUTYL 2.NITRILE
Respirator:	Type AEK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.

PROPERTIES



Mixes with water.
 Corrosive.
 Alkaline.Does not burn.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Supportive care. Irrigate eyes with saline. Supportive care.
Fire Fighting:	Keep surrounding area cool. Water spray/fog.
Spills and Disposal:	Prevent from entering drains. Contain spillage by any means.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive



Radioactive



Oxidizing

x

x

x

x — Must not be stored together