

Emulsotron KWZ-1258

INGREDIENTS	CAS NO	%	8HR OEL
toluene	108-88-3	25-35	191 mg/m3
methanol	67-56-1	30-40	262 mg/m3
solvent naphtha petroleum, heavy aromatic	64742-94-5	<5	-



UN No: **1992**
 Hazchem Code: ***3W**
 DG Class: **3**
 Subsidiary Risk: **6.1**
 Packing Group: **III**
 Poisons Schedule: **S6**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

PROPERTIES



Does not mix with water.
 Floats on water. Flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Wipe-off with clean/dry cloth. Remove contaminated clothing. Wash with water & soap. MEDICAL ATTENTION.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. Decontaminate with ipecac or lavage. Ethanol therapy.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable Explosive Toxic Radioactive Oxidizing

x x x x x

x — Must not be stored together

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 Toxic by inhalation, in contact with skin and if swallowed.
 Irritating to eyes and skin.
 Toxic: Danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
 HARMFUL-May cause lung damage if swallowed.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 Possible risk of harm to the unborn child.

* — limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.PE/EVAL/PE 2.SARANEX-232-PLY

Respirator:

Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion Hazard:

Flammable.
 Toxic smoke/fumes in a fire.

Environment:

Harmful to aquatic organisms.
 May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.