

Sigma Empire Satin paint

INGREDIENTS	CAS NO	%	8HR OEL
isoparaffins petroleum hydrotreated HFP	64742-47-8.	2.5-10	790 mg/m3
naphtha petroleum, isoparaffin, hydrotreated	64742-48-9.	<30	-
fatty acids, C6-19-branched, calcium salts	68409-80-3	<2.5	-
methyl ethyl ketoxime	96-29-7	<1	-



UN No: 1263 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION







Effects:

Vapours may cause drowsiness and dizziness.

Chronic **Health Effects:** Repeated exposure may cause skin dryness and cracking.

* - limited evidence

PRECAUTIONS FOR USE















Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
Fire/Explosion Hazard:	Flammable. Toxic smoke/fumes in a fire.
Environment:	Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES









Does not mix with water. Sinks in water.Flammable.

EMERGENCY









FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To	Evaluate for respiratory distress. Consider lavage with cuffed tube, NO adrenalin

Fire Fighting: Foam.

> Spills and Disposal:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means.

Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









x

Toxic Radioactive Oxidizing

X X

- Must not be stored together