

CLEAR CEMENT# 999128

INGREDIENTS	CAS NO	%	8HR OEL
cyclohexanone	108-94-1	<50	100 mg/m3
tetrahydrofuran	109-99-9	<50	295 mg/m3
methyl ethyl ketone	78-93-3	>50	445 mg/m3
polyvinyl chloride	9002-86-2	<50	-



UN No: 1993

Hazchem Code: •3YE

DG Class: 3

Subsidiary Risk: **Not Applicable**

Packing Group: II

Poisons Schedule: S5



NFPA Rating:

▶ 0: Minimum

▶ 1: Low

▶ 2: Moderate

▶ 3: High

▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation, in contact with skin and if swallowed.

Irritating to eyes, respiratory system and skin. HARMFUL-May cause lung damage if swallowed. Vapours may cause drowsiness and dizziness.

Chronic Health Effects:

Possible risk of harm to the unborn child. Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PROPERTIES



Mixes with water. Highly flammable.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Fire Fighting:	Keep containers cool. Water spray/ fog. Foam - alcohol type.
Spills and Disposal:	Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog.

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.PE/EVAL/PE 2.NITRILE

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.

Fire/Explosion Hazard:

HIGHLY FLAMMABLE.
Toxic smoke/fumes in a fire.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together