

Henkel Loctite Locquic Primer T 7471 Aerosol

INGREDIENTS	CAS NO	%	8HR OEL
acetone	67-64-1	>60	1185 mg/m ³
isopropanol	67-63-0	5-10	983 mg/m ³
iso-butane	75-28-5	10-30	-



UN No: 1950
 Hazchem Code: 2Y
 DG Class: 2.1
 Subsidiary Risk: **None**
 Packing Group: **None**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects: Irritating to eyes.
 Vapours may cause drowsiness and dizziness.

Chronic Health Effects: Repeated exposure may cause skin dryness and cracking.

* – limited evidence

PRECAUTIONS FOR USE



Glasses: Consider chemical goggles.

Gloves: 1.PVDC/PE/PVDC 2.PE/EVAL/PE

Respirator: Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container in a well ventilated place. Keep away from heat. Keep away from sources of ignition. No smoking.

Fire/Explosion Hazard: HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Risk of explosion if heated under confinement. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

PROPERTIES



2
 Extremely flammable.

EMERGENCY



FIRST AID

Swallowed: Do NOT give milk or oil. Do NOT give alcohol.

Skin: Wash with soap & water. Apply cleansing cream.

Advice To Doctor: No antidote. Supportive care.

Fire Fighting: Keep containers cool. Water spray/ fog. Foam - alcohol type.

Spills and Disposal: Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Use only in well ventilated areas. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive

x



Toxic

x



Radioactive

x



Oxidizing

x

x — Must not be stored together