

Wetico Berko Safe 104A Scale Inhibitor

INGREDIENTS	CAS NO	%	8HR OEL
2-phosphonobutane-1,2,4-tricarboxylic acid	37971-36-1	20-50	-
hydroxyethanediphosphonic acid	2809-21-4	20-50	-
AA-AMPS	40623-75-4	20-50	-



UN No: 1760 Hazchem Code: 2X DG Class: 8

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable

NFPA Rating:

- ▶ 0: Minimum
- ▶ 2: Moderate
- ▶ **3:** High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION









Harmful if swallowed.

Causes burns.

Risk of serious damage to eyes.

PRECAUTIONS FOR USE













Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider full face-shield.
Gloves:	PVC chemical resistant type.
Respirator:	Type AB-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep away from food, drink and animal feeding stuffs.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire. Attacks metals to liberate hydrogen. Dispose of this material and its container at hazardous or special waste collection point.
Environment:	May cause long-term adverse effects in the aquatic environment. May cause long-term adverse effects in the environment. Use appropriate container to avoid environmental contamination. Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES





Liquid. Mixes with water. Corrosive. Acid.Combustible.

EMERGENCY











FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Airway problems - 100% O2. Treat burns as thermal. Retract eyelids - irrigate 30 mins. Retract eyelids/ Irrigate 30 mins.
Fire Fighting:	Water spray/ fog.
Spills and	Eliminate ignition sources. Pollutant. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Neutralize with soda ash/ lime. Stop leak if safe to do so. Dispose of this material and its

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water.





Disposal:

Explosive Radioactive x x

x — Must not be stored together