

GLYPTAL NO. 1201

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	<60	350 mg/m3
talc	14807-96-6	1-10	3 mg/m3
naphtha petroleum, light aliphatic solvent	64742-89-8.	1-10	-



UN No: 1263
 Hazchem Code: •3Y
 DG Class: 3
 Subsidiary Risk: **Not Applicable**
 Packing Group: III
 Poisons Schedule: S5



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful by inhalation and in contact with skin.
 Irritating to eyes and skin.
 HARMFUL-May cause lung damage if swallowed.

Chronic Health Effects:

Possible risk of harm to the unborn child.
 * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.PE/EVAL/PE 2.PVA 3.TEFLON

Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.
 Restrictions on Storage apply. Refer to Full Report.
 Use only in well ventilated areas.
 Dispose of this material and its container at hazardous or special waste collection point.
 Keep out of reach of children.
 Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable.
 Vapours/gas heavier than air.
 Toxic smoke/fumes in a fire.
 Use only in well ventilated areas.
 Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES



Liquid.
 Does not mix with water.
 Sinks in water.Flammable.

EMERGENCY



FIRST AID

Swallowed:

Give water (if conscious). Seek medical advice.
 Do NOT give milk or oil.
 Do NOT give alcohol.

Eye:

Wash with running water (15 mins). Medical attention.

Skin:

Remove contaminated clothing. Wash with soap & water.

Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting:

Foam.

Spills and Disposal:

Eliminate ignition sources.
 Prevent from entering drains.
 Contain spillage by any means.
 Absorb with dry agent.
 Stop leak if safe to do so.
 Use only in well ventilated areas.
 Dispose of this material and its container at hazardous or special waste collection point.
 This material and its container must be disposed of in a safe way.
 To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive

Toxic

Radioactive

Oxidizing

x

x

x

x

x — Must not be stored together