

BTR167 valve sealant

INGREDIENTS	CAS NO	%	8HR OEL
lithium hydroxystearate	7620-77-1	10-15	10 mg/m3
calcium stearate	1592-23-0	1-2	10 mg/m3
tallowalkyldimethylammonium chloride/ bentonite quaternary	71011-24-0	15-25	-
propylene carbonate	108-32-7	9-11	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Chronic Health Effects: Harmful: danger of serious damage to health by prolonged exposure through inhalation.

* – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls: General Exhaust Ventilation adequate.

Glasses: Consider chemical goggles.

Gloves: PVC chemical resistant type.

Respirator: Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area.

Fire/Explosion Hazard: Toxic smoke/fumes in a fire.

Environment: Toxic to aquatic organisms. Use appropriate container to avoid environmental contamination.

PROPERTIES



Solid.
Does not mix with water.
Sinks in water.

EMERGENCY



FIRST AID

Swallowed: Give water (if conscious). Seek medical advice.

Eye: Wash with running water (15 mins). Medical attention.

Skin: Remove contaminated clothing. Wash with soap & water.

Inhaled: Fresh air. Rest, keep warm.

Advice To Doctor: Treat symptomatically.

Spills and Disposal: Avoid dust.
Sweep shovel to safe place.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable Explosive Radioactive Oxidizing

x

x

x

x

x — Must not be stored together