

PPG CA 8000B Curing Solution

INGREDIENTS	CAS NO	%	8HR OEL
hexamethylene diisocyanate polymer	28182-81-2	>60	0.02 mg/m3
n-butyl acetate	123-86-4	1-<10	713 mg/m3
cumene	98-82-8	<1	125 mg/m3
1,2,4-trimethyl benzene	95-63-6	1-<10	-



UN No: 1263 Hazchem Code: •3Y DG Class: 3 Subsidiary Risk: None

Packing Group: III Poisons Schedule: S6



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION







Acute Health Effects: Harmful by inhalation.

May cause SENSITISATION by inhalation. May cause SENSITISATION by skin contact.

May cause CANCER.

Chronic **Health Effects:** Harmful: danger of serious damage to health by prolonged exposure through inhalation.

* - limited evidence

PRECAUTIONS FOR USE













Appropriate
engineering
controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.PE/EVAL/PE 2.PVA 3.TEFLON

Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or

national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Toxic smoke/fumes in a fire. Reacts with water. Dispose of this material and its container at hazardous or special waste collection

PROPERTIES





Liquid.Flammable.







FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.

Fresh air. Rest, keep warm. If breathing shallow, Inhaled: give oxygen. Medical attention.

Advice To Doctor:

For asthma inhale sympathomimetics Charcoal and cathartics for ingestion For corneal injury -

mydriatics, analgesics.

Fire Fighting: Foam.

Spills and

Disposal:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its

container must be disposed of in a safe way. To clean the floor and all objects contaminated by this

material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive







Toxic Radioactive Oxidizing X Х