

## Schlumberger Corrosion Inhibitor A283

INGREDIENTS	CAS NO	%	8HR OEL
naphtha, petroleum, hydrodesulfurised heavy	64742-82-1.	30-60	900 mg/m3
ethylbenzene	100-41-4	5-10	434 mg/m3
xylene	1330-20-7	1-5	350 mg/m3
isopropanol	67-63-0	5-10	983 mg/m3



UN No: 1993  
 Hazchem Code: 3Y  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: III  
 Poisons Schedule: S6



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION



## Acute Health Effects:

Irritating to eyes.  
 Irritating to skin.  
 HARMFUL-May cause lung damage if swallowed.  
 Vapours may cause drowsiness and dizziness.

## Chronic Health Effects:

Limited evidence of a carcinogenic effect.  
 Repeated exposure may cause skin dryness and cracking.

\* – limited evidence

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.PVA 2.PE/EVAL/PE 3.VITON

## Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

## Fire/Explosion Hazard:

Flammable. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

## PROPERTIES



Liquid. Does not mix with water. Floats on water. Flammable.

## EMERGENCY



## FIRST AID

## Swallowed:

Give water (if conscious). URGENT MEDICAL ATTENTION. Do NOT give milk or oil. Do NOT give alcohol.

## Eye:

Wash with running water.

## Skin:

Remove contaminated clothing. Wash with soap & water.

## Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

## Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

## Fire Fighting:

Foam.

## Spills and Disposal:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

Explosive	Toxic	Radioactive	Oxidizing
x	x	x	x

x — Must not be stored together