

## The Sherwin-Williams 981300 Series-Jet Flex Urethane Dark Gray BAC 703

INGREDIENTS	CAS NO	%	8HR OEL
cyclohexanone	108-94-1	<12	100 mg/m3
propylene glycol monomethyl ether acetate, alpha-isomer	108-65-6	<10	274 mg/m3
METHYL ETHYL KETONE	78-93-3	10-25	445 mg/m3
n-butyl acetate	123-86-4	10-25	713 mg/m3



UN No: 1263  
 Hazchem Code: \*3YE  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: II  
 Poisons Schedule: **Not Applicable**



### NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

### HEALTH HAZARD INFORMATION



#### Acute Health Effects:

Irritating to eyes.  
 Irritating to respiratory system.  
 HARMFUL-May cause lung damage if swallowed.  
 Vapours may cause drowsiness and dizziness.

#### Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
 May cause CANCER by inhalation.  
 Possible risk of harm to the unborn child.  
 Repeated exposure may cause skin dryness and cracking.

\* — limited evidence

### PRECAUTIONS FOR USE



#### Appropriate engineering controls:

Local Exhaust Ventilation recommended.

#### Glasses:

Consider chemical goggles.

#### Gloves:

1.VITON/CHLOROBUTYL 2.VITON

#### Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

#### Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container in a well ventilated place. Keep away from food, drink and animal feeding stuffs. Keep away from sources of ignition. No smoking. Handle and open container with care.

#### Fire/Explosion Hazard:

HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

#### Environment:

May cause long-term adverse effects in the aquatic environment.  
 May cause long-term adverse effects in the environment. Use appropriate container to avoid environmental contamination.  
 Avoid release to the environment. Refer to special instructions/Safety data sheets.

### PROPERTIES



Liquid.R11R19

### EMERGENCY



### FIRST AID

**Swallowed:** Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

**Eye:** Wash with running water.

**Skin:** Remove contaminated clothing. Wash with soap & water.

**Inhaled:** Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.

**Advice To Doctor:** Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. Assist ventilation Hypotension - Trendelenburg Position. Methylene blue for severe poisoning.

**Fire Fighting:** Keep containers cool. Foam.

Eliminate ignition sources. Consider evacuation. Pollutant. Prevent from entering drains. Contain spillage by any means. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

### SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive Toxic Radioactive Oxidizing

x — Must not be stored together