

Sunoco Sunaplex 781

INGREDIENTS	CAS NO	%	8HR OEL
paraffinic distillate, heavy, hydrotreated (severe)	64742-54-7.	50-70	5 mg/m3
residual oils, petroleum, hydrotreated	64742-57-0	15-25	5 mg/m3
zinc oxide	1314-13-2	1-5	10 mg/m3
aluminium benzoate C16-18-fatty acids hydroxy complexes	82980-54-9	5-10	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects: Vapours may cause drowsiness and dizziness.

Chronic Health Effects: May cause CANCER.
 * — *limited evidence*

PRECAUTIONS FOR USE



Glasses: Consider chemical goggles.

Gloves: PVC chemical resistant type.

Respirator: Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area.

Fire/Explosion Hazard: Toxic smoke/fumes in a fire.

Environment: Harmful to aquatic organisms.
 May cause long-term adverse effects in the aquatic environment. Use appropriate container to avoid environmental contamination.

PROPERTIES



Does not mix with water.
 Floats on water. Combustible.

EMERGENCY



FIRST AID

Swallowed: Give water (if conscious). Seek medical advice.

Eye: Wash with running water.

Skin: Wash with soap

Inhaled: Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

Advice To Doctor: Emesis generally unnecessary. Debride for subcutaneous injection.
 Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

Fire Fighting: Foam.

Spills and Disposal: Eliminate ignition sources.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Oxidizing

x

x — *Must not be stored together*