

Carlisle Syntec Sure-Seal EM-8 Hypalon Color Coating

INGREDIENTS	CAS NO	%	8HR OEL
carbon tetrachloride	56-23-5	<.09	0.63 mg/m3
methyl isobutyl ketone	108-10-1	15-40	205 mg/m3
xylene	1330-20-7	10-20	350 mg/m3
isobutanol	78-83-1	5-10	152 mg/m3



UN No: 1263 Hazchem Code: •3YE DG Class: 3 Subsidiary Risk: Not Applicable

Packing Group: II Poisons Schedule: S5

NFPA Rating:

- ▶ 0: Minimum
- ▶1: Low
- ▶ 2: Moderate
- **▶3:** High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION























Harmful by inhalation, in contact with skin and if swallowed.

Irritating to respiratory system and skin. Acute Health Risk of serious damage to eyes Effects:

HARMFUL-May cause lung damage if swallowed.

Vapours may cause drowsiness and dizziness.

Danger of cumulative effects.

Limited evidence of a carcinogenic effect.

Harmful: danger of serious damage to health by prolonged exposure

through inhalation, in contact with skin and if swallowed.

Chronic Health May cause harm to the unborn child. Effects: Possible risk of impaired fertility.

Repeated exposure may cause skin dryness and cracking.

*- limited evidence

PRECAUTIONS FOR USE



т













engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.VITON
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Fransportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report.
	HIGHLY ELAMMARI E

Fire/Explosion Vapours/gas heavier than air. Hazard: Toxic smoke/fumes in a fire.

Toxic to aquatic organisms.

May cause long-term adverse effects in the aquatic environment. Dangerous for the ozone layer. Use appropriate container to avoid

Environment: environmental contamination.

Avoid release to the environment. Refer to special instructions/Safety

data sheets.

PROPERTIES







Liquid.

Mixes with water. Highly flammable.

EMERGENCY











RST	ΛI	\mathbf{n}

Give water (if conscious). Seek medical advice. Swallowed:

Do NOT give milk or oil.

Do NOT give alcohol.

Eye: Wash with running water (15 mins). Medical attention. Skin: Remove contaminated clothing. Wash with soap & water.

Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical Inhaled:

Advice To

Doctor:

Keep containers cool.

Water spray/ fog. Fire Fighting: Foam - alcohol type

Eliminate ignition sources.

Consider evacuation.

Pollutant.

Spills and Prevent from entering drains. Disposal:

Contain spillage by any means. Absorb with dry agent.

Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS











Flammable Explosive Toxic Radioactive Oxidizing Х x x Х

Must not be stored together