

PPG 101000 Mulco Flextra Thermoplastic Multipurpose Exterior Extradurable Sealant Clear

INGREDIENTS	CAS NO	%	8HR OEL
xylene	1330-20-7	15-40	350 mg/m3
ethylbenzene	100-41-4	3-7	434 mg/m3
toluene	108-88-3	0.1-1	191 mg/m3
white mineral oil (petroleum)	8042-47-5	3-7	5 mg/m3



UN No: 1133 Hazchem Code: •3Y DG Class: 3

Subsidiary Risk: Not Applicable

Packing Group: III Poisons Schedule: \$5



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION













Acute Health Effects: Harmful by inhalation. Harmful in contact with skin.

Irritating to eyes. Irritating to skin.

Vapours may cause drowsiness and dizziness.

Chronic **Health Effects:** Limited evidence of a carcinogenic effect. Harmful: danger of serious damage to health by prolonged exposure through inhalation.

* - limited evidence

PRECAUTIONS FOR USE













Appropriate
engineering
controls:

Local Exhaust Ventilation recommended.

Glasses:

Consider chemical goggles.

Gloves:

1.VITON 2.TEFLON 3.PE/EVAL/PE

Respirator:

Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88

or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.

Fire/Explosion Hazard:

Flammable. Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

Environment:

Harmful to aquatic organisms.

PROPERTIES











EMERGENCY











FIRST AID

Give water (if conscious). URGENT MEDICAL Swallowed: ATTENTION. Wash with running water. Eye:

Remove contaminated clothing. Wash with soap & Skin:

Fresh air. Rest, keep warm. If breathing shallow, Inhaled:

give oxygen. Medical attention.

Advice To Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin. Doctor:

Fire Fighting: Foam.

Spills and

Disposal:

Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its

container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS









Explosive

Toxic х

Radioactive Oxidizing Х

- Must not be stored together