


CMCI Cemtec Damp-Proofing Bit Coating

INGREDIENTS	CAS NO	%	8HR OEL
bitumen road making	8052-42-4	55	5 mg/m3
water	7732-18-5	35	-
rubber	Not Available	10	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Vapours may cause drowsiness and dizziness.

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.BUTYL 2.NEOPRENE 3.VITON
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.

PROPERTIES



Liquid.
Mixes with water. Does not burn.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water. For burns: Apply cold water. Do NOT remove clothes from area. Cover wound. NO OINTMENTS.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Treat symptomatically. Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Keep surrounding area cool. Water spray/fog.
Spills and Disposal:	Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Oxidizing

x

x — Must not be stored together