

USG Sheetrock All Purpose Joint Compound Ready Mixed

INGREDIENTS	CAS NO	%	8HR OEL
gypsum	13397-24-5	}	10 mg/m3
vinyl acetate	108-05-4	<0.1	35 mg/m3
acetaldehyde	75-07-0	<0.1	36 mg/m3
gypsum	13397-24-5	NotSpec.	10 mg/m3

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION



Acute Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation. Irritating to respiratory system and skin. Risk of serious damage to eyes.

Chronic Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 * – limited evidence

PRECAUTIONS FOR USE



Appropriate engineering controls:

General Exhaust Ventilation adequate.

Glasses:

Consider chemical goggles.

Gloves:

PVC chemical resistant type.

Respirator:

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Storage and Transportation:

Store in cool, dry, protected area.

PROPERTIES

Does not burn.

EMERGENCY



FIRST AID

Swallowed:	Rinse mouth with water.
Eye:	Wash with running water (15 mins). Medical attention.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breath shallow, give oxygen. Medical attention.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Keep surrounding area cool. Water spray/fog.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Flammable Explosive Radioactive Oxidizing

x x x x

x — Must not be stored together