

LUBRICATING OIL-200

INGREDIENTS	CAS NO	%	8HR OEL
molybdenum(VI) oxide	1313-27-5	10-19	10 mg/m3
cobalt (II) oxide	1307-96-6	1-5	-



UN No: 3077 Hazchem Code: 2Z DG Class: 9

Subsidiary Risk: Not Applicable

Packing Group: III

Poisons Schedule: Not Applicable

NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ **3**: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION













Chronic

Health Effects:

Harmful: danger of serious damage to health by prolonged exposure through inhalation and if swallowed

May cause SENSITISATION by skin contact.

Danger of cumulative effects.

Limited evidence of a carcinogenic effect. Harmful: danger of serious damage to health by prolonged exposure through inhalation and if

swallowed.

* – limited evidence

PRECAUTIONS FOR USE











Glasses:

Consider chemical goggles.

Respirator:

Particulate. (AS/NZS 1716 & 1715, EN 143:000 & 149:001, ANSI Z88 or national equivalent)

Storage and Transportation: Store in cool, dry, protected area.

Restrictions on Storage apply. Refer to Full Report.

Toxic to aquatic organisms.

Environment:

May cause long-term adverse effects in the aquatic environment. Use appropriate container to

avoid environmental contamination.

Avoid release to the environment. Refer to special instructions/Safety data sheets.

PROPERTIES





Does not mix with water. Floats on water Does not burn.

EMERGENCY









FIRST AID

Swallowed: Give water (if conscious). Seek medical advice.

> Wash with running water. Eye:

Remove contaminated clothing. Wash with soap & Skin:

Fresh air. Rest, keep warm. Inhaled:

Advice To Doctor:

Treat symptomatically.

Fire Fighting:

Keep containers cool. Keep surrounding area cool. Water spray/fog.

Pollutant.

Spills and Disposal:

Prevent from entering drains. Contain spillage by any means.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS







Х



Flammable Explosive Radioactive Oxidizing х

- Must not be stored together