

## Saudi Industrial Paint Sipoxy Shield 240 Base

INGREDIENTS	CAS NO	%	8HR OEL
METHYL ISOBUTYL KETONE	108-10-1	4.7	205 mg/m3
XYLENE	1330-20-7	2.5	350 mg/m3



UN No: 1993  
 Hazchem Code: •3YE  
 DG Class: 3  
 Subsidiary Risk: **Not Applicable**  
 Packing Group: II  
 Poisons Schedule: **Not Applicable**



## NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

## HEALTH HAZARD INFORMATION

## Chronic Health Effects:

Limited evidence of a carcinogenic effect.  
 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

\* – limited evidence

## PRECAUTIONS FOR USE



## Appropriate engineering controls:

Local Exhaust Ventilation recommended.

## Glasses:

Consider chemical goggles.

## Gloves:

1.PE/EVAL/PE 2.PVA 3.TEFLON

## Respirator:

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

## Storage and Transportation:

Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children. Keep container in a well ventilated place. Keep away from sources of ignition. No smoking.

## Fire/Explosion Hazard:

HIGHLY FLAMMABLE. Vapours/gas heavier than air. Toxic smoke/fumes in a fire. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. In case of fire and/or explosion, DO NOT BREATHE FUMES.

## PROPERTIES



Liquid. Does not mix with water. Sinks in water. Highly flammable.

## EMERGENCY



## FIRST AID

## Swallowed:

Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.

## Eye:

Wash with running water.

## Skin:

Remove contaminated clothing. Wash with soap & water.

## Inhaled:

Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.

## Advice To Doctor:

Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.

## Fire Fighting:

Keep containers cool. Foam.

## Spills and Disposal:

Eliminate ignition sources. Consider evacuation. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. Take precautionary measures against static discharges. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

## SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Explosive

Toxic

Radioactive

Oxidizing

x

x

x

x

x — Must not be stored together