

ExxonMobil Mobilith SHC 100

INGREDIENTS	CAS NO	%	8HR OEL
4,4'-methylene bis(dibutyldithiocarbamate)	10254-57-6	1-<5	-
octylated diphenylamines	68411-46-1	1-<5	-
zinc dialkyl dithiophosphate	68649-42-3	1-<2.5	-
lithium hydroxide	1310-66-3	0.1-<1	-

UN No: Not Applicable Hazchem Code: Not Applicable DG Class: Not Applicable Subsidiary Risk: Not Applicable Packing Group: Not Applicable Poisons Schedule: Not Applicable



NFPA Rating:

- ▶ 0: Minimum
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE











Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Dispose of this material and its container at hazardous or special waste collection point. Keep out of reach of children.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire. Dispose of this material and its container at hazardous or special waste collection point.

PROPERTIES







Liquid. Does not mix with water. Sinks in water. Combustible.

EMERGENCY









RST	ΛI	
16.71	_	

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm.
Advice To Doctor:	Emesis generally unnecessary. Debride for subcutaneous injection.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. Dispose of this material and its container at hazardous or special waste collection point. This material and its container must be disposed of in a safe way.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS

x — Must not be stored together