

Flowserve Nordstrom X-196RS Sealant

INGREDIENTS	CAS NO	%	8HR OEL
cellulose	9004-34-6	8-15	10 mg/m3
tallow alkyldimethylammonium chloride/ bentonite	68953-58-2	8-15	-
propylene carbonate	108-32-7	<1	-
vegetable oil	Not Available	55-85	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type AX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.

PROPERTIES



Does not mix with water.
 Sinks in water. Combustible.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Wash with soap
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Oxidizing

x

x — Must not be stored together