


Ardrox 6405

INGREDIENTS	CAS NO	%	8HR OEL
ethylene glycol monobutyl ether	111-76-2	5	96.9 mg/m3
diethylene glycol	111-46-6	5	100 mg/m3
sodium xylenesulfonate	1300-72-7	4	-
sodium metasilicate, anhydrous	6834-92-0	0.7	-

UN No: **Not Applicable**
 Hazchem Code: **Not Applicable**
 DG Class: **Not Applicable**
 Subsidiary Risk: **Not Applicable**
 Packing Group: **Not Applicable**
 Poisons Schedule: **Not Applicable**



NFPA Rating:

- ▶ 0: Minimum
- ▶ 1: Low
- ▶ 2: Moderate
- ▶ 3: High
- ▶ 4: Extreme

HEALTH HAZARD INFORMATION

PRECAUTIONS FOR USE



Appropriate engineering controls:	Local Exhaust Ventilation recommended.
Glasses:	Consider chemical goggles.
Gloves:	1.BUTYL
Respirator:	Type A-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area.
Fire/Explosion Hazard:	Vapours/gas heavier than air. Toxic smoke/fumes in a fire.

PROPERTIES



Liquid. Does not burn.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Treat symptomatically.
Fire Fighting:	Keep surrounding area cool. Water spray/fog.
Spills and Disposal:	Spilled liquid has low temperature and evaporates quickly. Control vapour with water spray/ fog. Absorb with dry agent. Stop leak if safe to do so.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



Oxidizing

x

x — Must not be stored together